

Product: X-LINE LED 2200 MICRO-PRM EDD 24 830 LINE-1EL / L-567MM Index: 19.4170.1213.24



Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Light and electrical data

	Category	Surface mounte	d lumir	aires					
	Family	X-LINE LED LIN	E						
	Name	X-LINE LED 220	0 MICR	O-PRM	EDD 24	830 LIN	NE-1EL	/ L-567I	MM
	Index	19.4170.1213.24							
		(6		$\langle E \rangle$	\bigcirc	IP	IK		
			LED			44	04	Indoor	Ľ
	Light sour	се		L	ED				
	Luminous flux LED [lm]			2203					
	LED power [W]			11,7					
	Luminaire luminous flux [lm]			1659					
	Luminane	iuminous nux [im]			059				
		uminaire [W]			2,6				

	L 3	
	LED power [W]	11,7
	Luminaire luminous flux [lm]	1659
F	Power of luminaire [W]	12,6
	Luminaire's light efficiency [lm/W]	131,7
	Color of the light [K]	3000
С	RI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
Pr	otection degree	IP44
,	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000 (1) / 147000 (2)
	Lx/By	L80/B10 (1) / L70/B50 (2)
C	Dperating temperature range [°C]	5 ÷ 30
C	Driver	DIM DALI (EDD)
ſ	Power factor cos φ	>0,9
	Circuit load capacity	14 (B10), 24 (B16), 22 (C10), 36 (C16)



Mechanical data	Пîн	Assembly	directly mounted to ceiling construction or surface mounted on slings			
A	└ <u></u> ←→ B	Material	aluminum			
	U	Color	anodised aluminum			
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)			
		Impact resistant	IK04			
		Weight [kg]	1,62			
		Dimensions [mm]	567 x 63 x 74			
A graph of light			105° 90° 75° 60° 45° 45° 45° 300 45° 45° 45° 45° 45° 45° 45° 45°			



Accessories










Index 6E1-500KWAN1P-B Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT



Name X-LINE Clamp for line luminaires




Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023