

Product: X-LINE LED 8800 MICRO-PRM EDD 24 840 LINE-1S / L-2242MM Index: 19.4172.5223.24



Description

Lx/By

Driver

Power factor $\cos \phi$

Circuit load capacity

Operating temperature range [°C]

Category Surface mounted luminaires

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Light and electrical data

5,									
Family	X-LINE LED LINE								
Name	X-LINE LED 8800 MICRO-PRM EDD 24 840 LINE-1S / L-2242MM								
Index	19.4172.522	3.24							
		E	E		P ₄₄	K ₀₄	Indoor		
Light sour	се		L	ED					
Luminous flux LED [lm]			ę	9130					
LED power [W]			4	46,8					
Luminaire luminous flux [lm]			6	6877					
Power of luminaire [W]			4	49,1					
Luminaire's light efficiency [lm/W]			1	140,1					
Color of the light [K]			4	4000					
CRI			>	>80					
SDCM (LE	ED sources)		3	3					
Beam angle [°]			((C0-C180) / (C90-C270) - 82,8° / 97,2°					
Photobiolo 62471)	ogical risk clas	s (IEC/EN	RG0						
Protection	against electr	ic shock	I						
Protection degree			I	IP44					
Voltage			2	220240 V, 5060 Hz					
Lifetime of	f LED sources	[h]	1	LOOOOO (1) / 147	000 (2)			

L80/B10 (1) / L70/B50 (2)

14 (B10), 23 (B16), 22 (C10), 35

5 ÷ 30

>0,95

(C16)

DIM DALI (EDD)



Mechanical data	Пîн	Assembly	directly mounted to ceiling construction or surface mounted on slings			
Α	└ <u>┘</u> +⊓ ++ B	Material	aluminum anodised aluminum			
		Color				
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)			
		Impact resistant	IK04			
		Weight [kg]	5,29			
		Dimensions [mm]	2242 x 63 x 74			
A graph of light			90° -0° -0° -0° -0° -0° -0° -0° -			



Accessories










Index 6E1-500KWAN1P-B Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT



Name X-LINE Clamp for line luminaires




Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023