

Product: X-LINE LED 1950 MICRO-PRM EDD 24 840 LINE-1S / CONNECTOR TYPE-LC 600/300 Index: 19.4176.2123.24



Description


Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Product information	Category Surface mounted luminaires		
	Family X-LINE LED CONNECTOR L		
	Name X-LINE LED 1950 MICRO-PRM EDD 24 840 LINE-1S / CONNEC TYPE-LC 600/300		
	Index 19.4176.2123.24		
	$\underbrace{K}_{LED} \underbrace{K}_{H} \underbrace{K}_{H}$	Indoor	
Light and electrical data	Light source LED		
	Luminous flux LED [lm] 1964		
	LED power [W] 10,3		
	Luminaire luminous flux [Im] 1479		
	Power of luminaire [W] 11,1		
	Luminaire's light efficiency [lm/W] 133,2		
	Color of the light [K] 4000		
	CRI >80		
	SDCM (LED sources) 3		
	Beam angle [°] (C0-C180) / (C90-C270) - 82	2,8° / 97,2°	
	Protection against electric shock		
	Protection degree IP44		
	Voltage 220240 V, 5060 Hz		
	Lifetime of LED sources [h] 100000 (1) / 147000 (2)		
	Lx/By L80/B10 (1) / L70/B50 (2)		
	Operating temperature range [°C] 5 ÷ 30		
	Driver DIM DALI (EDD)		
	Power factor $\cos \varphi$ >0,95		
	Circuit load capacity 14 (B10), 24 (B16), 22 (C10), 36 (C16)	
Mechanical data	Assembly directly mounted to ceiling constr surface mounted on slings	uction or	
∢ A►	Material aluminum		
	Color anodised aluminum	anodised aluminum	
	Diffuser Micro-PRM (micro-prismatic diffus	Micro-PRM (micro-prismatic diffuser PMMA)	
	Impact resistant IK04		

Dimensions [mm]

593 x 313 x 71

A graph of light







Accessories










Index 6E1-500KWAN1P-B Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT



Name X-LINE Clamp for line luminaires




Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023