

Product: X-LINE LED 3300 PLX E 24 840 LINE-S / CONNECTOR TYPE-LD 600/300

Index: 19.4176.5221.24



Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Product information

Category	Surface mounted luminaires
Family	X-LINE LED CONNECTOR L
Name	X-LINE LED 3300 PLX E 24 840 LINE-S / CONNECTOR TYPE-LD 600/300
Index	19 4176 5221 24
















Light and electrical data

LED
3436
17,4
2290
19,2
119,3
4000
>80
3
(C0-C180) / (C90-C270) - 109° / 107,2°
I
IP44
220240 V, 5060 Hz
100000 (1) / 147000 (2)
L80/B10 (1) / L70/B50 (2)
5 ÷ 30
standard on/off (E)
>0,95


Mechanical data



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	593 x 313 x 71



A graph of light







Accessories


Index 6E1-500KWAN1P-3

Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT




Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24
LENGHT 1,5M WITHOUT WIRE 1POINT




Index 0E1XLL-SLED

Name X-LINE Clamp for line luminaires



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

