

## Product: X-LINE LED 4400 PLX EDD 24 840 LINE-1S / CONNECTOR TYPE-LB 600/600 Index: 19.4176.7623.24



## Description


Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Product information	Category Surface mounte	d luminaires
	Family X-LINE LED CON	
		0 PLX EDD 24 840 LINE-1S / CONNECTOR TYPE-
	Index 19.4176.7623.24	
	CE	$\begin{array}{c} \\ \blacksquare \end{array} \end{array} \begin{array}{c} \\ \blacksquare \end{array} \begin{array}{c} \blacksquare \end{array} \end{array} \begin{array}{c} \blacksquare \end{array} \begin{array}{c} \blacksquare \end{array} \end{array} \begin{array}{c} \blacksquare \end{array} \begin{array}{c} \blacksquare \end{array} \end{array} \begin{array}{c} \blacksquare \end{array} \end{array} \begin{array}{c} \blacksquare \end{array} \end{array} \begin{array}{c} \blacksquare \end{array} \end{array} $
Light and electrical data	Light source	LED
	Luminous flux LED [lm]	4565
	LED power [W]	23,4
	Luminaire luminous flux [lm]	] 3043
	Power of luminaire [W]	24,7
	Luminaire's light efficiency [	[lm/W] <b>123,2</b>
	Color of the light [K]	4000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 109° / 107,2°
	Protection against electric s	hock I
	Protection degree	IP44
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000 (1) / 147000 (2)
	Lx/By	L80/B10 (1) / L70/B50 (2)
	Operating temperature rang	ge [°C] 5 ÷ 30
	Driver	DIM DALI (EDD)
	Power factor $\cos \phi$	>0,95
	Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)
Mechanical data	Assembly	directly mounted to ceiling construction or surface mounted on slings
	Material	aluminum
	Color	anodised aluminum
	Diffuser	PLX (PMMA opal)
	Impact resistant	IK04
	D:	

Dimensions [mm]

593 x 593 x 71

## A graph of light







## Accessories










Index 6E1-500KWAN1P-B Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT



Name X-LINE Clamp for line luminaires




Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023