

Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM EDD 24 840 LINE-1S / L-574MM S-1,5M

Index: 19.4179.1623.24



### **Description**

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via EL-marked luminaire.

#### **Product information**

Category Surface mounted luminaires

Family X-LINE SLIM LED LINE

Name X-LINE SLIM L-DOWN LED 2200 MICRO-PRM EDD 24 840 LINE-1S / L-574MM S-1,5M

Index 19.4179.1623.24
















## Light and electrical data

LED
2283
11,7
1697
12,6
134,7
4000
>80
3
(C0-C180) / (C90-C270) - 88,4° / 86°
I
IP40
220240 V, 5060 Hz
100000 (1) / 147000 (2)
L80/B10 (1) / L70/B10 (2)
5 ÷ 30
DIM DALI (EDD)
>0,95
14 (B10), 24 (B16), 22 (C10), 36 (C16)

#### Mechanical data






Assembly	surface mounted on slings
Material	aluminum
Color	anodised aluminum
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	574 x 48 x 70



# A graph of light







#### **Accessories**


Index 6E1-500KWAN1P-5

Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT




Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT

