

Product: X-LINE WALL UP OR DOWN LED 1300 PLX EDD 24 840 / L-572MM**Index:** 19.4188.1223.24

Description

Luminary to be mounted on wall. Its body made from anodized aluminum profile. Luminary equipped with highly efficient LED sources. Its no frame diffuser is made from white polymethyl methacrylate with a great light transparency. Luminary is characterized by high illumination efficacy. Purpose: offices, conference rooms, corridors, halls, etc.

Product information

Category	Surface mounted luminaires
Family	X-LINE WALL UP OR DOWN LED
Name	X-LINE WALL UP OR DOWN LED 1300 PLX EDD 24 840 / L-572MM
Index	19.4188.1223.24



Light and electrical data

Light source	LED
Luminous flux LED [lm]	1420
LED power [W]	8
Luminaire luminous flux [lm]	947
Power of luminaire [W]	9
Luminaire's light efficiency [lm/W]	105,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109° / 107,2°
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,9
Circuit load capacity	14 (B10), 24 (B16), 22 (C10), 36 (C16)

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1,6
Dimensions [mm]	572 x 63 x 74

A graph of light

