

**Product:** X-LINE LED COMPACT 4000 MICRO-PRM E 34 840 / L-1132MM

**Index:** 19.4189.3121.34



## Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver. X-LINE fittings are intended to be mounted on ceiling or pendants. In the family of X-LINE LED fittings modules of renowned brands are applied.

## Product information


|          |                                                              |
|----------|--------------------------------------------------------------|
| Category | <b>Compact</b>                                               |
| Family   | <b>X-LINE LED COMPACT</b>                                    |
| Name     | <b>X-LINE LED COMPACT 4000 MICRO-PRM E 34 840 / L-1132MM</b> |
| Index    | <b>19.4189.3121.34</b>                                       |



## Light and electrical data


|                                     |                                               |
|-------------------------------------|-----------------------------------------------|
| Light source                        | <b>LED</b>                                    |
| Luminous flux LED [lm]              | <b>4118</b>                                   |
| LED power [W]                       | <b>25</b>                                     |
| Luminaire luminous flux [lm]        | <b>3102</b>                                   |
| Power of luminaire [W]              | <b>27</b>                                     |
| Luminaire's light efficiency [lm/W] | <b>114,9</b>                                  |
| Color of the light [K]              | <b>4000</b>                                   |
| CRI                                 | <b>&gt;80</b>                                 |
| SDCM (LED sources)                  | <b>3</b>                                      |
| Beam angle [°]                      | <b>(C0-C180) / (C90-C270) - 82,8° / 97,2°</b> |
| Protection against electric shock   | <b>I</b>                                      |
| Protection degree                   | <b>IP44</b>                                   |
| Voltage                             | <b>220..240 V, 50..60 Hz</b>                  |
| Lifetime of LED sources [h]         | <b>60000</b>                                  |
| Lx/By                               | <b>L80/B10</b>                                |
| Operating temperature range [°C]    | <b>5 ÷ 30</b>                                 |
| Driver                              | <b>standard on/off (E)</b>                    |
| Power factor cos φ                  | <b>&gt;0,95</b>                               |
| Circuit load capacity               | <b>22 (B10), 34 (B16), 33 (C10), 54 (C16)</b> |

## Mechanical data




|                  |                                                                              |
|------------------|------------------------------------------------------------------------------|
| Assembly         | <b>directly mounted to ceiling construction or surface mounted on slings</b> |
| Material         | <b>aluminum</b>                                                              |
| Color            | <b>RAL 9016 (white)</b>                                                      |
| Diffuser         | <b>Micro-PRM (micro-prismatic diffuser PMMA)</b>                             |
| Impact resistant | <b>IK04</b>                                                                  |
| Weight [kg]      | <b>3,1</b>                                                                   |
| Dimensions [mm]  | <b>1132 x 63 x 74</b>                                                        |

A graph of light



Accessories


Index 6E1-500KW34K-3  
Name SUSPENSION NEW TYPE-A+B 34  
LENGHT 1,5M WIRE 3X SET



Index 6E1-8670-B-1,5-3X  
Name SUSPENSION NEW TYPE-F  
LENGHT-1,5 METER WIRE 3X 1-  
POINT




Index 6E1-8670-B-1,5  
Name SUSPENSION NEW TYPE-E  
LENGHT-1,5 METER WITHOUT  
WIRE 1-POINT



Index 6E1-500KWB34K-3  
Name SUSPENSION NEW TYPE-A+E 34  
LENGHT 1,5M WIRE 3X SET



Index 6E1-9875-4-1,5-3X  
Name SUSPENSION NEW TYPE-D  
LENGHT-1,5 METER WIRE 3X 1-  
POINT



Index 6E1-9875-3-1,5  
Name SUSPENSION NEW TYPE-C  
LENGHT-1,5 METER WITHOUT  
WIRE 1-POINT

