

Product: X-LINE SLIM SURFACE LED COMPACT 4000 PLX E 34 840 / L-1418MM

Index: 19.4191.2221.34



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED Compact, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim Compact uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim Compact luminaire is designed for mounting directly to ceiling.

Product information

Category	Compact
Family	X-LINE SLIM SURFACE LED COMPACT
Name	X-LINE SLIM SURFACE LED COMPACT 4000 PLX E 34 840 / L-1418MM
Index	19.4191.2221.34



Light and electrical data

Light source	LED
Luminous flux LED [lm]	4606
LED power [W]	24
Luminaire luminous flux [lm]	2955
Power of luminaire [W]	26
Luminaire's light efficiency [lm/W]	113,7
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
Protection against electric shock	I
Protection degree	IP40
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	2,05
Dimensions [mm]	1418 x 48 x 70

A graph of light

