

Product: RUBIN SPORT NEW LED 16000 MICRO-PRM KR E 34 830 / 1190X220MM

Index: 19.4206.2111.34



Description

Surface mounted luminary dedicated for the sports, gymnastics and squash halls, etc. Luminary equipped with the protecting grid made from steel wire powder coated. Diffuser used in the luminary provides less glare effect for the room users when compared to the light sources used in the fluorescents.

Product information

Category Industrial luminaires

Family RUBIN SPORT NEW LED

Name RUBIN SPORT NEW LED 16000 MICRO-PRM KR E 34 830 / 1190X220MM

Index 19.4206.2111.34
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	16104
LED power [W]	102
Luminaire luminous flux [lm]	12094
Power of luminaire [W]	114
Luminaire's light efficiency [lm/W]	106,1
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 90,2° / 99,6°
Protection against electric shock	1
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	14 (B10), 22 (B16), 14 (C10), 22 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK10
Weight [kg]	7,5
Dimensions [mm]	1190 x 220 x 60



A graph of light

