

Product: RUBIN SPORT NEW LED 16000 MICRO-PRM KR E 34 840 / 1190X220MM Index: 19.4206.2121.34



Description

Surface mounted luminary dedicated for the sports, gymnastics and squash halls, etc. Luminary equipped with the protecting grid made from steel wire powder coated. Diffuser used in the luminary provides less glare effect for the room users when compared to the light sources used in the fluorescents.

Product information	Cate	Category Industrial luminaires			
	Fami	y RUBIN SPORT NEV	ORT NEW LED		
	Name	RUBIN SPORT NEV	V LED 16000 MICRO-PRM KR E 34 840 /		
	Index	19.4206.2121.34			
Light and electrical data	Light	source	LED		
	Lumi	nous flux LED [lm]	16660		
	LED	power [W]	102		
	Lumi	naire luminous flux [lm]	12512		
	Powe	er of luminaire [W]	114		
	Lumi	naire's light efficiency [lm/	109.8		

Assembly sur	face mounted on ceiling
Circuit load capacity	14 (B10), 22 (B16), 14 (C10), 22 (C16
Power factor $\cos \phi$	>0,95
Driver	standard on/off (E)
Operating temperature range [°C]	5 ÷ 30
Lx/By	L80/B10 (1) / L70/B50 (2)
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Voltage	220240 V, 5060 Hz
Protection degree	IP20
Protection against electric shock	I
Beam angle [°]	(C0-C180) / (C90-C270) - 90,2° / 99,6°
SDCM (LED sources)	3
CRI	>80
Color of the light [K]	4000
Luminaire's light efficiency [lm/W]	109,8
_	Color of the light [K] CRI SDCM (LED sources) Beam angle [°] Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C] Driver Power factor cos φ Circuit load capacity

Ţн

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK10
Weight [kg]	7,3
Dimensions [mm]	1190 x 220 x 60

A graph of light



