

## Product: RUBIN SPORT NEW LED 16000 MICRO-PRM KR EDD 34 840 / 1190X220MM Index: 19.4206.2123.34



## Description

Surface mounted luminary dedicated for the sports, gymnastics and squash halls, etc. Luminary equipped with the protecting grid made from steel wire powder coated. Diffuser used in the luminary provides less glare effect for the room users when compared to the light sources used in the fluorescents.

Product information	Categor Family	Category Industrial luminaires Family RUBIN SPORT NEW LED		
	Name	RUBIN SPORT NEW LED 16000 MICRO-PRM KR EDD 34 840 / 1190X220MM		
	Index	19.4206.2123.34 $\overbrace{ED} \bigoplus \bigoplus$		
Light and electrical data	Light so	urce LED us flux LED [lm] 16660		

Light and electrical data	Light source	LED
	Luminous flux LED	[lm] 16660
	LED power [W]	102
	Luminaire luminous	flux [lm] 12512
	Power of luminaire [	[W] 114
	Luminaire's light effi	iciency [lm/W] 109,8
	Color of the light [K]	4000
	CRI	>80
	SDCM (LED source	s) <b>3</b>
	Beam angle [°]	(C0-C180) / (C90-C270) - 90,2° / 99,6°
	Protection against e	electric shock I
	Protection degree	IP20
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sou	rces [h] <b>100000 (1) / 147000 (2)</b>
	Lx/By	L80/B10 (1) / L70/B50 (2)
	Operating temperat	ure range [°C] 5 ÷ 30
	Driver	DIM DALI (EDD)
	Power factor $\cos \phi$	>0,95
	Circuit load capacity	/ 18 (B10), 32 (B16), 18 (C10), 32 (C16)
Mechanical data	Assembly	surface mounted on ceiling
В	Material	steel sheet
	Color	RAL 9016 (white)
	Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
	H Impact resistant	IK10
A	Weight [kg]	7,5
	0 1 01	•

Dimensions [mm]

1190 x 220 x 60

## A graph of light



