

Product: RUBIN SPORT NEW LED 24000 MICRO-PRM KR EDD 34 830 / 1190X320 Index: 19.4206.3113.34



Description

Surface mounted luminary dedicated for the sports, gymnastics and squash halls, etc. Luminary equipped with the protecting grid made from steel wire powder coated. Diffuser used in the luminary provides less glare effect for the room users when compared to the light sources used in the fluorescents.

Product information	Category	Category Industrial luminaires		
	Family	RUBIN SPORT NEW LED		
	Name	RUBIN SPORT NEW LED 24000 MICRO-PRM KR EDD 34 830 / 1190X320		
	Index	19.4206.3113.34		
Light and electrical data	Light sou	burce LED		
	Luminou	bus flux LED [lm] 24156		
		152		

		Luminous flux LED [im]	24156
		LED power [W]	153
		Luminaire luminous flux [Im]	18141
		Power of luminaire [W]	171
		Luminaire's light efficiency [lm/	/W] 106,1
		Color of the light [K]	3000
		CRI	>80
		SDCM (LED sources)	3
		Beam angle [°]	(C0-C180) / (C90-C270) - 90,2° / 99,6°
		Protection against electric sho	ck I
		Protection degree	IP20
		Voltage	220240 V, 5060 Hz
		Lifetime of LED sources [h]	100000 (1) / 147000 (2)
		Lx/By	L80/B10 (1) / L70/B50 (2)
	Operating temperature range	[°C] 5÷30	
		Driver	DIM DALI (EDD)
		Power factor $\cos \phi$	>0,95
		Circuit load capacity	9 (B10), 16 (B16), 9 (C10), 16 (C16)
Mechanical data		Assembly	surface mounted on ceiling
		Material	steel sheet
		Color	RAL 9016 (white)
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
	[]] H	Impact resistant	IK10

Dimensions [mm]

1190 x 320 x 60

A graph of light



