

## Product: RUBIN SPORT NEW LED 16000 PC-T MICRO-PRM IP44 STRONG E 34 830 / 1190X220 Index: 19.4207.1211.34



## Description

Surface mounted luminary dedicated for sports halls, gyms and schools. The body is made of powder-coated steel sheet. The luminary is equipped with a PC and PMMA diffuser (with a microprismatic structure) with an additional stiffening mount, which does not require a protective grid.

Product information	Category Industrial luminaires		
	Family RUBIN SPORT NEW LE	Family RUBIN SPORT NEW LED	
	Name RUBIN SPORT NEW LE 34 830 / 1190X220	ED 16000 PC-T MICRO-PRM IP44 STRONG E	
	Index 19.4207.1211.34		
Light and electrical data	Light source	LED	
	Luminous flux LED [lm]	16104	
	LED power [W]	102	
	Luminaire luminous flux [lm]	11107	
	Power of luminaire [W]	114	
	Luminaire's light efficiency [lm/W]	97,4	
	Color of the light [K]	3000	
	CRI	>80	
	SDCM (LED sources)	3	
	Beam angle [°]	(C0-C180) / (C90-C270) - 90,2° / 99,6°	
	Protection against electric shock	I	
	Protection degree	IP44	
	Voltage	220240 V, 5060 Hz	
	Lifetime of LED sources [h]	100000 (1) / 147000 (2)	
	Lx/By	L80/B10 (1) / L70/B50 (2)	
	Operating temperature range [°C]	5 ÷ 30	
	Driver	standard on/off (E)	
	Power factor $\cos \phi$	>0,95	
	Circuit load capacity	14 (B10), 22 (B16), 14 (C10), 22 (C16)	

Ťн

## **Mechanical data**



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PC-T MICRO-PRM (transparent polycarbonate and micro-prismatic diffuser PMMA)
Impact resistant	IK10
Weight [kg]	7,6
Dimensions [mm]	1190 x 220 x 60

## A graph of light



