

Product: RUBIN SPORT NEW LED 16000 PC-T MICRO-PRM IP44 STRONG E 34 840 / 1190X220 Index: 19.4207.1221.34



Description

Surface mounted luminary dedicated for sports halls, gyms and schools. The body is made of powder-coated steel sheet. The luminary is equipped with a PC and PMMA diffuser (with a microprismatic structure) with an additional stiffening mount, which does not require a protective grid.

Product information	Category	Category Industrial luminaires		
	Family	RUBIN SPORT NEW LED		
	Name	Name RUBIN SPORT NEW LED 16000 PC-T MICRO-PRM IP44 STRONG I 34 840 / 1190X220		
	Index	19.4207.1221.34		
			$\textcircled{E} \textcircled{P}_{44} \H{K}_0 \textcircled{E}_{\text{Indoor}} \textcircled{B}$	
Light and electrical data	Light sou	irce	LED	
-	Luminou	s flux <mark>LED [lm]</mark>	16660	
	LED pow	ver [W]	102	
	Luminair	e luminous flux [lm]	11490	
	Power of	luminaire [W]	114	
	Luminair	e's light efficiency [lm/W]	100,8	
	Color of	the light [K]	4000	

	Material	steel sheet
Mechanical data	Assembly	surface mounted on ceiling
	Circuit load capacity	14 (B10), 22 (B16), 14 (C10), 22 (C16)
	Power factor $\cos \phi$	>0,95
	Driver	standard on/off (E)
	Operating temperatur	e range [°C] 5 ÷ 30
	Lx/By	L80/B10 (1) / L70/B50 (2)
	Lifetime of LED source	es [h] 100000 (1) / 147000 (2)
	Voltage	220240 V, 5060 Hz
	Protection degree	IP44
	Protection against ele	ctric shock I
	Beam angle [°]	(C0-C180) / (C90-C270) - 90,2° / 99,6°
	SDCM (LED sources)	3
	CRI	>80
	Color of the light [K]	4000

Ţн

	в
	 ł
Α	

Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PC-T MICRO-PRM (transparent polycarbonate and micro-prismatic diffuser PMMA)
Impact resistant	IK10
Weight [kg]	7,6
Dimensions [mm]	1190 x 220 x 60

A graph of light



