


**Product:** RUBIN SPORT NEW LED 24000 PC-T MICRO-PRM IP44 STRONG E 34 830 / 1190X220

**Index:** 19.4207.2211.34



## Description

Surface mounted luminary dedicated for sports halls, gyms and schools. The body is made of powder-coated steel sheet. The luminaire is equipped with a PC and PMMA diffuser (with a microprismatic structure) with an additional stiffening mount, which does not require a protective grid.

## Product information

Category	Industrial luminaires
Family	RUBIN SPORT NEW LED
Name	RUBIN SPORT NEW LED 24000 PC-T MICRO-PRM IP44 STRONG E 34 830 / 1190X220
Index	19.4207.2211.34



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	24156
LED power [W]	153
Luminaire luminous flux [lm]	16660
Power of luminaire [W]	171
Luminaire's light efficiency [lm/W]	97,4
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 90,2° / 99,6°
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	7 (B10), 11 (B16), 7 (C10), 11 (C16)

## Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PC-T MICRO-PRM (transparent polycarbonate and micro-prismatic diffuser PMMA)
Impact resistant	IK10
Dimensions [mm]	1190 x 220 x 60

## A graph of light

